

Climate chamber with illumination

The BINDER climate chamber with illumination of the KBW series achieves homogeneous light distribution with its natural illumination. That allows this climate chamber to create constant lighting and temperature conditions.



Advantages:

- Homogeneous light distribution
- Natural growth conditions
- Temperature & light in one unit

Areas of application:



Cosmetics Industry



Plant / Insect Growth



Packaging Industry


Features	Customer benefits	Characteristics
APT.line™ climate technology	<ul style="list-style-type: none"> • Same test conditions throughout the chamber interior • Independent of specimen size and quantity • No drying out of specimens 	APT.line™ <ul style="list-style-type: none"> • Constant and gentle circulation of air through large-surface side walls even under a full load • Homogeneous climate conditions throughout all specimens
Light	<ul style="list-style-type: none"> • Up to 20% greater usable space • Light sources adjustable to specimen sizes • Same irradiation results throughout the chamber interior 	<ul style="list-style-type: none"> • Flexible positioning and fully removeable illumination cassettes • Excellent light uniformity for all specimens on the entire shelf • Different light spectra can be used
Cooling system	<ul style="list-style-type: none"> • Reliable testing independent of ambient conditions 	<ul style="list-style-type: none"> • Powerful compressor cooling system with large power reserves for lighting applications • No freezing thanks to double evaporator plate • Carefully measured cooling
Standard equipment	<ul style="list-style-type: none"> • No extra costs • Chamber is easily moved on casters 	Comprehensive standards <ul style="list-style-type: none"> • Communication interface • Access port diameter 30 mm • BINDER test certificate • Casters • Inner glass door and double outer door seal • Door heated against condensation
Unit design	<ul style="list-style-type: none"> • Minimum space requirements • Easy assembly • Large chamber interior volume • Easy cleaning 	<ul style="list-style-type: none"> • Optimal ratio of usable space and footprint • Large access area thanks to wide design • Chamber interior made out of high-quality stainless steel • Closed illumination cassettes • No permanent fixtures
Accessories and Services	<ul style="list-style-type: none"> • Complete solution • Everything from one source • BINDER Service is always nearby 	Comprehensive product portfolio <ul style="list-style-type: none"> • Various options: BINDER Data Logger Kits, access ports in various sizes and positions, control and documentation software APT-COM™ • Years of proven and recognized validation and documentation materials • Worldwide service network

- Electronically controlled APT.line™ preheating chamber assuring temperature accuracy and reproducible results
- Temperature range 0 °C to 70 °C (without illumination)
- Temperature range 5 °C to 60 °C (with illumination)
- 3 variable positioned illumination cassettes with 5 daylight illumination tubes, each, in steps switchable
- The patented illumination system assures an unique homogeneous light distribution
- MP controller with 2 programs with 10 sections each, alternatively switchable to 1 program with 20 sections
 - Integrated week program timer with real time function
 - Digital temperature setting with an accuracy of a tenth of a degree
 - Adjustable ramp functions via program editor
 - Adjustable fan speed
 - Elapsed time indicator
- Access port Ø 30 mm, left side
- Inner glass door
- Independent adjustable temperature safety device class 3.1, providing full protection against chamber over-temperature, with visual and audible temperature alarm
- RS 422 interface for communication software APT-COM™ DataControlSystem
- Adjustable intervals for printer
- 3 stainless steel racks
- BINDER test confirmation

KBW 720 (E5.1)


▶ Exterior dimensions	
Width (mm)	1255
Height (incl. casters) (mm)	1925
Depth (incl. door handle, I-triangle, connection 80 mm) (mm)	890
Wall clearance, rear (mm)	100
Wall clearance, side (mm)	100
Steam space volume (l)	918
Number of doors (ea.)	2
Inner glass door(s) (ea.)	2

Heat compensation with illumination



▶ Interior dimensions	
Width (mm)	973
Height (mm)	1250
Depth (mm)	576
Interior volume (l)	698
Racks (number standard/max.)	3 / 12
Load per rack (kg)	45
Permitted total load (kg)	150
Weight (empty) (kg)	377
Variable position illumination cassettes	3

Heat compensation without illumination



▶ Temperature data (without illumination)	
Temperature range (°C)	0 - 70
Temperature variation (± K)	0,5
Temperature fluctuation (± K)	0,1
Max. heat compensation up to 40 °C (W)	750

▶ Temperature data (with 100 % illumination)	
Temperature range (°C)	5 - 60
Temperature variation (± K)	1
Temperature fluctuation (± K)	0,1
Max. heat compensation up to 40 °C (W)	500
Illumination data (per illumination cassette)	

Daylight tubes (Lux) / (W/m ²)	14.200 / 38
Fluora® growth lamps (Lux) / (W/m ²)	10.500 / 31
Arabidopsis tubes (Lux) / (W/m ²)	14.400 / 38

KBW 720 (E5.1)

▶ Electrical data	
IP protection class acc. to EN 60529	IP 20
Voltage ($\pm 10\%$) 50 / 60 Hz (V)	200 - 240, 1 N ~
Nominal power (kW)	2,7
Energy consumption 1)	
without illumination at 0 °C (W)	455
with illumination at 4 °C (W)	880
with illumination at 25 °C (W)	820
with illumination at 37 °C (W)	885
Noise level (dB (A))	53

1) These values can be used for dimensioning air condition systems.

All technical data are specified for units with standard equipment at an ambient temperature of 25 °C and a line voltage fluctuation of $\pm 10\%$. The temperature data is determined in accordance to factory standard following DIN 12880, respecting the recommended wall clearances of 10% of the height, width and depth of the inner chamber. All figures are typical average values for series devices. We reserve the right to alter technical specifications at any time.



Variable illumination

The illumination selection is based on the application, light spectrum and intensity. For example: FLUORA® growth fluorescent tubes may be exchanged for daylight fluorescent tubes




BINDER Data Logger Kits

The new BINDER Data Logger Kits – Makes independent recording of temperature and humidity data in the BINDER device possible. The tailored product solution contains helpful accessories: from mounting the logger to the BINDER device to cable access assistance to the sensor mount



Access port

With silicone plugs for introducing external measuring instruments into the chamber, access ports with 30, 50 or 100 mm diameters



Analog output

Analog output for temperature 4 - 20 mA with 6-pin DIN socket (output not adjustable)



Calibration certificate & validation

BINDER can significantly reduce the workload in qualifying and validating devices. Nobody knows our devices as well and has as much experience in certifications as we do

KBW 720 (E5.1)

Access ports with silicone plug 30, 50, 100 mm	<input type="radio"/>
Securing elements for additional fastening of racks (1 set of 4 pieces)	<input type="radio"/>
Additional PT 100 temperature sensor, flexibly installed, with external connection, including DIN connector (6-pin)	<input type="radio"/>
Ethernet interface for communication software APTCOM™ DataControlSystem	<input type="radio"/>
Factory calibration certificate. Measurement in center of chamber at 37 °C or at specified testing temperature	<input type="radio"/>
Extension to factory calibration certificate. Each additional measurement at an additional measuring point or temperature	<input type="radio"/>
Temperature measurement acc. to DIN 12880 (27 measuring points) at 37 °C or at specified temperature with measuring protocol and certificate	<input type="radio"/>
Data Logger Kit T 220: For the continuous temperature recording of -90 °C to 220 °C. Kit includes 1 data logger, PT 100 sensor with 2 m Teflon extension cable and 1 fixture for the connection at the BINDER unit	<input type="radio"/>
Data Logger converter cable RS 232 to USB 2.0	<input type="radio"/>
Data Logger Software: Configuration und evaluation software for all BINDER Data Logger Kits, incl. data cable (RS 232)	<input type="radio"/>
Rack, stainless steel	<input type="radio"/>
Shelf, perforated, stainless steel	<input type="radio"/>
Reinforced rack, stainless steel, with 1 set of securing elements (1 set of 4 pieces), max. load 70 kg	<input type="radio"/>
Vibration compatible shelf / platform (positioned at bottom level) to be mounted inside the chamber for shaker / spinner / roller operation. Other positions available on request	<input type="radio"/>
Temperature safety device, class 3.3 (DIN 12880) with optical alarm	<input type="radio"/>
Analog temperature output, 4-20 mA, with 6-pin DIN socket (output not adjustable)	<input type="radio"/>
Zero-voltage relay outputs accessible via 6-pin DIN socket. Additional module for controlling 2 relay outputs via 2 of the programmable controller's controller contacts. Outputs can be switched on and off either automatically, or also manually	<input type="radio"/>
Waterproof interior socket 230 V AC (max. 200 W), IP65 protected, with corresponding plug (IP66 protected) Max. allowed operating temperature 50 °C	<input type="radio"/>
FLUORA® growth lamps set as replacement for the standard tubes for 230 V	<input type="radio"/>
Arabidopsis fluorescent tubes set as replacement for the standard tubes for 230 V	<input type="radio"/>
Replacement set of standard daylight illumination tubes for one illumination cassette	<input type="radio"/>
Replacement set of FLUORA® illumination tubes for one illumination cassette	<input type="radio"/>
Replacement set of Arabidopsis illumination tubes for one illumination cassette	<input type="radio"/>
Locking door handle with key	<input type="radio"/>