


## Model FD 720 | Drying and heating chambers with forced convection

A BINDER FD series Avantgarde.Line heating oven is always used when fast drying and sterilization is required. Thanks to its fully homogeneous temperature distribution, quick dynamics and powerful fan, this heating oven saves valuable time.

### BENEFITS

- Best energy efficiency on the market
- Excellent temporal and spatial temperature accuracy
- USB connection for recording data
- Temperature range up to +300 °C



Model 720

### IMPORTANT FEATURES

- Temperature range: +10°C above ambient temperature to +300 °C
- High temperature accuracy thanks to APT.line™ technology
- Forced convection
- Controller with LCD display
- Electromechanical control of the exhaust air flap
- 2 chrome-plated racks
- Units up to 115 L are stackable
- Class 2 independent temperature safety device (DIN 12880) with visual temperature alarm
- Ergonomic handle design
- USB port for recording data

### ORDERING INFORMATION

| Interior volume |     | Power supply - unit fuse       | Plug*                   | Version  | Model version | Art.-No.  |
|-----------------|-----|--------------------------------|-------------------------|----------|---------------|-----------|
| [cu.ft.]        | [L] |                                |                         |          |               |           |
| Model FD 720    |     |                                |                         |          |               |           |
| 26              | 741 | 400 V 3~/N/PE 50/60 Hz -16,0 A | CEE 16 / 6 H plug 5-pin | Standard | FD720-400V    | 9010-0311 |


**TECHNICAL DATA**

| Data                                                  |                                            |
|-------------------------------------------------------|--------------------------------------------|
| Article Number                                        | 9010-0311                                  |
| Designation                                           | FD720-400V                                 |
| Option model                                          | Standard                                   |
| Performance Data Temperature                          |                                            |
| Temperature range                                     | +12 °C above ambient temperature to 300 °C |
| Temperature uniformity at 150°C                       | 2.5 ± K                                    |
| Temperature fluctuation at 150°C                      | 0.6 ± K                                    |
| Heating up time to 150°C                              | 25 min                                     |
| Recovery time after door was opened for 30 s at 150°C | 6 min                                      |
| Air change data                                       |                                            |
| Air change rate at 100°C                              | 5 x/h                                      |
| Electrical data                                       |                                            |
| Rated Voltage                                         | 400 V                                      |
| Power frequency                                       | 50/60 Hz                                   |
| Nominal power                                         | 4,5 kW                                     |
| Unit fuse                                             | 16,0 A                                     |
| Phase (Nominal voltage)                               | 3~/N/PE                                    |
| Dimensions and weights                                |                                            |
| Interior volume                                       | 26 cu.ft.                                  |
| Net weight of the unit (empty)                        | 366 lbs                                    |
| Load per rack                                         | 99 lbs                                     |
| Permitted load                                        | 694 lbs                                    |
| Wall clearance back                                   | 6,3 in                                     |
| Wall clearance sidewise                               | 3,94 in                                    |
| Housing dimensions not incl. fittings and connections |                                            |
| Width net                                             | 45.87 in                                   |
| Height net                                            | 62.6 in                                    |
| Depth net                                             | 34.25 in                                   |
| Internal Dimensions                                   |                                            |

|                               |          |
|-------------------------------|----------|
| Interior width                | 39.37 in |
| Interior height               | 51.18 in |
| Interior depth                | 22.44 in |
| Unit doors                    | 2        |
| Environment-specific data     |          |
| Sound-pressure level          | 43 dB(A) |
| Energy consumption at 100°C   | 480 Wh/h |
| Energy consumption at 150°C   | 800 Wh/h |
| Fixtures                      |          |
| Number of shelves (std./max.) | 2/16     |

All technical data is specified for unloaded units with standard equipment at an ambient temperature of +22 °C ±3 °C and a power supply voltage fluctuation of ±10 %. The temperature data is determined to BINDER factory standard following DIN 12880, observing the recommended wall clearances of 10 % of the height, width, and depth of the inner chamber. Technical data refers to 100 % fan speed. All indications are average values, typical for units produced in series. We reserve the right to change technical specifications at any time.

DIMENSIONS Incl. fittings and connections [mm]



OPTIONS

| Designation | Description                    | *  | Art.-No.  |
|-------------|--------------------------------|----|-----------|
|             | left                           |    |           |
|             | 10 mm                          | 01 | 8012-1276 |
|             | 30 mm                          | 01 | 8012-1016 |
|             | 50 mm                          | 01 | 8012-1020 |
|             | Access port with silicone plug | 01 | 8012-1027 |
|             | right                          |    |           |
|             | 10 mm                          | 01 | 8012-1269 |
|             | 30 mm                          | 01 | 8012-1015 |
|             | 50 mm                          | 01 | 8012-1019 |

| Designation                                     | Description                                                                                                                                                                 | *  | Art.-No.  |
|-------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|-----------|
|                                                 | 100 mm                                                                                                                                                                      | 01 | 8012-1028 |
|                                                 | top                                                                                                                                                                         |    |           |
|                                                 | 10 mm                                                                                                                                                                       | 01 | 8012-1263 |
|                                                 | 30 mm                                                                                                                                                                       | 01 | 8012-1364 |
|                                                 | 50 mm                                                                                                                                                                       | 01 | 8012-1380 |
|                                                 | 100 mm                                                                                                                                                                      | 01 | 8012-1671 |
| Alarm function for overheating                  | Switchable acoustic alarm, with adjustable limit value on the independent temperature safety device                                                                         | -  | 8012-1636 |
| Analog output 4-20 mA                           | for temperature values (output not adjustable)                                                                                                                              | 02 | 8012-1624 |
| Calibration certificate, expanded               | for temperature; for extending the measurement in center of chamber to include another test temperature                                                                     | -  | 8012-1116 |
|                                                 | for temperature, measurement in center of chamber at specified temperature                                                                                                  | -  | 8012-1135 |
| Calibration certificate, temperature            | temperature measurement incl. certificate, 9 measuring points at specified temperature                                                                                      | -  | 8012-1552 |
|                                                 | temperature measurement incl. certificate, 15- 18 measuring points at specified temperature                                                                                 | -  | 8012-1573 |
|                                                 | temperature measurement incl. certificate and 27 measuring points at specified temperature                                                                                  | -  | 8012-1594 |
| Class 3.1 independent temperature safety device | with visual alarm (DIN 12880)                                                                                                                                               | -  | 8012-1643 |
| Clock                                           | battery-backed                                                                                                                                                              | -  | 8012-1641 |
| Door lock                                       | lockable door handle                                                                                                                                                        | -  | 8012-1818 |
| Ethernet interface                              | for Multi Management Software APT-COM™                                                                                                                                      | -  | 8012-0989 |
| Fan, reinforced                                 | for increased air change rates, incl. uprated heat output for faster heating up time and improved recovery time; max. 300°C; not in conjunction with load management option |    |           |
|                                                 | 400 V option model                                                                                                                                                          | -  | 8012-1062 |
| HEPA air filter                                 | On fresh air supply for unit; filter classification H14 (acc. to. EN 1822-1:2009, > 99.995% at 0.3 µm); not in conjunction with reinforced heating output, reinforced fan   | -  | 8012-1099 |
| Inner chamber, reinforced                       | max. total load 350 kg                                                                                                                                                      | -  | 8012-1821 |
| Interior lighting                               | with two 27 W light bulbs                                                                                                                                                   |    |           |
|                                                 | 400 V option model                                                                                                                                                          | -  | 8012-1825 |
| Measurement of air exchange rate                | in accordance with ASTM D5374, definition and protocol according to ambient temperature                                                                                     | -  | 8012-1195 |
| Pt 100 temperature sensor                       | additional flexible Pt 100, interior, for displaying the temperature on the unit display                                                                                    | -  | 8012-1620 |
| Viewing window and interior lighting            | viewing window (triple insulating glass) in door, 300 x 480 mm, and 30 W interior lighting                                                                                  |    |           |

| Designation | Description        | * | Art.-No.  |
|-------------|--------------------|---|-----------|
|             | 400 V option model | - | 8012-1831 |

## ACCESSORIES

| Designation                      | Description                                                                                                                                                                                                                                                                                                                                          | * | Art.-No.  |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---|-----------|
| APT-COM™ 4 BASIC-Edition         | for simple logging and documentation requirements with up to 5 networked units.                                                                                                                                                                                                                                                                      |   |           |
|                                  | version 4, BASIC edition                                                                                                                                                                                                                                                                                                                             | - | 9053-0039 |
| APT-COM™ 4 GLP-Edition           | for working under GLP-compliant conditions. Measured values are documented in a tamper-proof way in line with the requirements of FDA Regulation 21 CFR 11.                                                                                                                                                                                          |   |           |
|                                  | version 4, GLP edition                                                                                                                                                                                                                                                                                                                               | - | 9053-0042 |
| APT-COM™ 4 PROFESSIONAL-Edition  | convenient unit and user management built on the BASIC edition. Suitable for networking up to 100 units.                                                                                                                                                                                                                                             |   |           |
|                                  | version 4, PROFESSIONAL edition                                                                                                                                                                                                                                                                                                                      | - | 9053-0040 |
| pH-neutral detergent             | concentrated, for gentle remove of residual contaminants; 1 kg                                                                                                                                                                                                                                                                                       | - | 8012-2250 |
| Qualification documents IQ/OQ    | IQ/OQ documents digital in PDF format – supporting documents for validation consisting of: IQ/OQ checklists, comprehensive unit documentation covering: temperature. Excluded: Document execution is separate                                                                                                                                        |   |           |
|                                  | temperature. Excluded: Document execution is separate                                                                                                                                                                                                                                                                                                | - | 7057-0010 |
| Qualification documents IQ/OQ/PQ | IQ/OQ/PQ documents digital in PDF format – supporting documents for validation customized to customer requirements, PQ section added to the qualification folder IQ/OQ; supporting documents for validation consisting of: IQ/OQ checklists, comprehensive unit documentation covering: temperature values. Excluded: Document execution is separate |   |           |
|                                  | temperature values. Excluded: Document execution is separate                                                                                                                                                                                                                                                                                         | - | 7057-0016 |
| Rack                             | max. load per rack 45 kg                                                                                                                                                                                                                                                                                                                             |   |           |
|                                  | chrome plated                                                                                                                                                                                                                                                                                                                                        | - | 8012-2044 |
|                                  | stainless steel                                                                                                                                                                                                                                                                                                                                      | - | 8012-2170 |
| Rack, heavy load                 | max. load per rack 70 kg                                                                                                                                                                                                                                                                                                                             |   |           |
|                                  | Stainless steel                                                                                                                                                                                                                                                                                                                                      | - | 8012-2185 |
| Shelf, perforated                | max. load per rack 40 kg                                                                                                                                                                                                                                                                                                                             |   |           |
|                                  | Stainless steel                                                                                                                                                                                                                                                                                                                                      | - | 8012-2178 |

## SERVICES

| Designation             | Description                                                                                                                             | *  | Art.-No.  |
|-------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|----|-----------|
| Calibration services    |                                                                                                                                         |    |           |
| Temperature calibration | Calibration of one (1) test temperature specified by the user in center of chamber, including certificate Travel to be quoted separate. | 05 | DL30-0120 |

| Designation                                  | Description                                                                                                                                                                                                                                                                                                                                                   | *  | Art.-No.  |
|----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|-----------|
|                                              | Extension of calibration of one (1) additional test temperature specified by the user in the center of the usable space, including certificate Travel to be quoted separate.                                                                                                                                                                                  | 05 | DL30-0102 |
| Temperature measurement, 9 measuring points  | Temperature measurement with 9 measuring points with a set value specified by the user, including certificate. Travel to be quoted separate. A total of 3 shelves are required.                                                                                                                                                                               | 05 | DL30-0109 |
| Temperature measurement, 18 measuring points | Temperature measurement with 18 measuring points with a set value specified by the user, including certificate. Travel to be quoted separate. A total of 2 shelves are required.                                                                                                                                                                              | 05 | DL30-0118 |
| Temperature measurement, 27 measuring points | Temperature measurement with 27 measuring points with a set value specified by the user, including certificate. Travel to be quoted separate. A total of 3 shelves are required.                                                                                                                                                                              | 05 | DL30-0127 |
| <b>Installation services</b>                 |                                                                                                                                                                                                                                                                                                                                                               |    |           |
| Unit installation                            | Connect the unit to the customer-side connections (electricity, water, wastewater, gas), basic functions check, brief operating instructions. (excl.: unpacking, setup, controller instructions, programming, installation work) Travel to be quoted as separate.                                                                                             | 05 | DL10-0160 |
| Unit instructions                            | Instruction regarding operating principle and basic functions of the unit, operation of the control electronics including programming. Travel to be quoted as separate Limited to 3 hours.                                                                                                                                                                    | 05 | DL10-0540 |
| <b>Maintenance services</b>                  |                                                                                                                                                                                                                                                                                                                                                               |    |           |
| BRONZE 3-year maintenance contract           | Annual Device Inspection Includes Preventive Maintenance with Calibration Certificate. 10% Discount on Spare Parts and Labor for any additional Services needed Wear + tear parts to be purchased or billed to customer. Travel to be quoted as separate.                                                                                                     | 05 | DL20-0720 |
| GOLD 3-year maintenance contract             | Annual Device Inspection Includes Preventive Maintenance with Calibration Certificate of Temperature. 25% Discount on Spare Parts and Labor for any additional Services needed. One additional courtesy visit per year can be used for service visit or operator. Wear + tear parts to be purchased or billed to customer. Travel to be quoted separate.      | 05 | DL20-0910 |
| Preventive maintenance                       | One-off maintenance service in accordance with maintenance schedule. Visual inspection of mechanical and electrical components, testing of all key functions. Checking a test temperature specified by the user in center of usable space without certificate. Wear + tear parts need to be purchased or billed to customer. Travel to be quoted as separate. | 05 | DL20-0602 |
| SILVER 3-year maintenance contract           | Annual Device Inspection Includes Preventive Maintenance with Calibration Certificate 15% Discount on Spare Parts and Labor for any additional Services needed One additional courtesy visit per year can be used for service visit or operator training. Wear + tear parts to be purchased or billed to customer. Travel to be quoted separate.              | 05 | DL20-0810 |
| <b>Validation services</b>                   |                                                                                                                                                                                                                                                                                                                                                               |    |           |
| Execution of IQ/OQ                           | Execution of IQ/OQ in accordance with qualification folder. Travel to be quoted separate.                                                                                                                                                                                                                                                                     | 05 | DL40-0100 |
| Execution of IQ/OQ/PQ                        | Execution of IQ/OQ/PQ in accordance with qualification folder. Travel to be quoted separate.                                                                                                                                                                                                                                                                  | 05 | DL44-0500 |
| <b>Warranty service</b>                      |                                                                                                                                                                                                                                                                                                                                                               |    |           |
| 1-year warranty extension                    | The warranty is extended by 1 year from the delivery date, wear parts are excluded                                                                                                                                                                                                                                                                            | 05 | DL50-0010 |

## NOTES

- 01      Condensation may occur in the area around the access port. Access ports may be placed in custom locations for an additional charge.
- 02      UL mark is not granted when this option is used.
- 05      Quoted prices do not include travel costs. Please refer to the chapter on BINDER Service for travel costs for your region. Quoted prices for services performed in Switzerland do not include a country-specific added fee (available on request).

### **BINDER GmbH**

Tuttlingen, Germany  
TEL +49 7462 2005 0  
info@binder-world.com  
www.binder-world.com

### **BINDER Inc.**

Bohemia, NY, USA  
TEL +1 631 224 4340  
usa@binder-world.com  
www.binder-world.us

### **BINDER Environmental Testing Equipment (Shanghai) Co., Ltd.**

Shanghai, P.R. China  
TEL +86 21 685 808 25  
china@binder-world.com  
www.binder-world.com