

# Model E 28 | Drying and heating chambers with mechanical adjustment

With a BINDER E series heating oven, you obtain a reliable and powerful unit in a solid configuration at a very attractive price. This heating oven is preferred for tasks in basic research, as well as in human and veterinary medicine.

## BENEFITS

- Uniform drying conditions thanks to APT.line™ technology
- Identical test conditions throughout the chamber interior independent of sample size and quantity
- Outstanding thermal insulation saves operation costs



Model 28



Model 28

## MAIN FEATURES

- Temperature range: 60 °C to 230 °C
- Adjustable exhaust air flap
- Hydro-mechanical thermostat
- Class 1 temperature limitation device (Model Eo28-230V-T)
- Timer 0 – 120 min
- 2 chrome-plated racks

## ORDERING INFORMATION

Interior volume [cu.ft.]	Voltage	Option model	Version	Art.-No.
1	230 V 1~ 50/60 Hz	Standard	Eo28-230V	9010-0001
		with TB class 1	Eo28-230V-T	9010-0003
	120 V 1~ 60 Hz	Standard	Eo28-120V	9010-0106

## TECHNICAL DATA


Description	Eo28-230V <sup>1</sup>	Eo28-230V-T <sup>1</sup>	Eo28-120V <sup>1</sup>
<b>Article Number</b>	<b>9010-0001</b>	<b>9010-0003</b>	<b>9010-0106</b>
<b>Performance Data Temperature</b>			
Temperature range	60...230	60...230	60...230
Heating-up time to 150 °C [min]	36	36	36
Recovery time after 30 seconds door open at 150 °C [min]	19	19	19

<sup>1</sup> All technical data is specified for unloaded units with standard equipment at an ambient temperature of +22 °C ±3 °C and a power supply voltage fluctuation of ±10%. The temperature data is determined in accordance to BINDER factory standard following DIN 12880, observing the recommended wall clearances of 10 % of the height, width, and depth of the inner chamber. All indications are average values, typical for units produced in series. We reserve the right to change technical specifications at any time.

Description	Eo28-230V <sup>1</sup>	Eo28-230V-T <sup>1</sup>	Eo28-120V <sup>1</sup>
Article Number	9010-0001	9010-0003	9010-0106
<b>Electrical data</b>			
Rated Voltage [V]	230	230	120
Power frequency [Hz]	50/60	50/60	60
Nominal power [kW]	0.8	0.8	0.8
Phase (Nominal voltage)	1~	1~	1~
<b>Measures</b>			
Interior volume [cu.ft.]	1	1	1
Net weight of the unit (empty) [lbs]	49	49	49
Permitted load [lbs]	55	55	55
Load per rack [lbs]	22	22	22
Wall clearance back [in]	6.3	6.3	6.3
Wall clearance sidewise [in]	3.94	3.94	3.94
<b>Internal Dimensions</b>			
Width [in]	15.76	15.76	15.76
Height [in]	11.03	11.03	11.03
Depth [in]	9.85	9.85	9.85
<b>Doors</b>			
Unit doors	1	1	1
<b>Housing dimensions not incl. fittings and connections</b>			
Width net [in]	22.85	22.85	22.85
Height net [in]	15.96	15.96	15.96
Depth net [in]	16.74	16.74	16.74
<b>Fixtures</b>			
Number of shelves (std./max.)	2/4	2/4	2/4

1 All technical data is specified for unloaded units with standard equipment at an ambient temperature of +22 °C ±3 °C and a power supply voltage fluctuation of ±10%. The temperature data is determined in accordance to BINDER factory standard following DIN 12880, observing the recommended wall clearances of 10 % of the height, width, and depth of the inner chamber. All indications are average values, typical for units produced in series. We reserve the right to change technical specifications at any time.

## DIMENSIONS INCL. FITTINGS AND CONNECTIONS [MM]



## OPTIONS

Designation	Description	*	Art.-No.
<b>Options/Accessories</b>	for temperature; for extending the measurement in center of chamber to include another test temperature	-	8012-1114
	Measurement in center of chamber at specified temperature	-	8012-1133

\* Notes › See last page

## ACCESSORIES

Designation	Description	*	Art.-No.
Options/Accessories	chrome plated	-	6004-0001
	Stainless steel	-	6004-0028
	concentrated, for gentle remove of residual contaminants; 1 kg	-	1002-0016
	set of 4 anti-slip feet, for safe stacking of units	-	8012-0702

\* Notes › See last page

## SERVICES

Designation	Description	*	Art.-No.
<b>Installation services</b>			
Services	Unit function instructions for operation and programming of the controller	18	DL10-0500
	Unpacking and setting up of unit, connecting to existing connections, and checking function	13, 18	DL10-0100
<b>Preventive maintenance</b>			
Services	Executive of equipment inspection according to maintenance plan	14, 18	DL20-0200
<b>Calibration services</b>			
Services	Expansion – including certificate, each additional measuring point in center of chamber at specified test temperature	14, 16, 17, 18	DL30-0102
	Temperature calibration with 1 measuring point in center of chamber at a specified test temperature, including certificate	14, 16, 17, 18	DL30-0101
<b>Warranty service</b>			
Services	The warranty is extended from 2 to 3 years from the delivery date, wear parts are excluded	-	DL00-1041
	The warranty is extended from 2 to 5 years from the delivery date, wear parts are excluded	-	DL00-1042

\* Notes › See last page

**NOTES**

- 01 Condensation may occur in the area around the access port. Access ports may be placed in custom locations for an additional charge.
- 02 UL mark is not granted when this option is used.
- 03 Heat resistant only to max. 200 °C.
- 04 Only available on units rated for 230 V.
- 07 The additional heat input may affect the temperature behavior.
- 09 Not in conjunction with the optional access port, door with window and interior lighting.
- 10 Not available on 23-liter units.
- 11 Not available on 23- or 53-liter units.
- 12 Only available on units rated for 230 V or 400 V.
- 13 Installation and connections take place at unit location; transport within the company only upon consultation.
- 14 We recommend a BINDER service contract to cover unit inspections, calibrations and validations.
- 15 OQ according to Yellow Paper = completed factory validation documentation of all OQ checklists.
- 16 Sensor calibration is performed in an accredited calibration laboratory.
- 17 Calibration is performed according to the BINDER factory standard.
- 18 Quoted prices do not include travel costs. Please refer to the chapter on BINDER Service for travel costs for your region. Quoted prices for services performed in Switzerland do not include a country-specific added fee (available on request).
- 19 For additional accessories, refer to the Process documentation chapter.

**BINDER GmbH**

Tuttlingen, Germany  
TEL +49 7462 2005 0  
FAX +49 7462 2005 100  
info@binder-world.com  
www.binder-world.com

**BINDER Asia Pacific (Hong Kong) Ltd.**

Kowloon, Hong Kong, P.R. China  
TEL +852 39070500  
FAX +852 39070507  
asia@binder-world.com  
www.binder-world.com

**Representative Office for CIS**

Moscow, Russia  
TEL +7 495 988 15 16  
FAX +7 495 988 15 17  
russia@binder-world.com  
www.binder-world.com

**BINDER Environmental Testing  
Equipment (Shanghai) Co., Ltd.**

Shanghai, P.R. China  
TEL +86 21 685 808 25  
FAX +86 21 685 808 29  
china@binder-world.com  
www.binder-world.com

**BINDER Inc.**

Bohemia, NY, USA  
TEL +1 631 224 4340  
FAX +1 631 224 4354  
usa@binder-world.com  
www.binder-world.us